



# SAFETY TAILGATE MEETING

Generated by Safety Compliance App [www.safetycompliance.com](http://www.safetycompliance.com) | [www.safetycomplianceapp.com](http://www.safetycomplianceapp.com)

Company	Four Star Rebar	Project	Entrada Apartments		
Date	February 10, 2023	Time	6:29 AM	Conductor	Fermin Salas

## CRANE SAFETY

### INTRODUCTION

**INTRODUCTION:** There are many different types of cranes that can be used. For example, there are tower cranes, crawler cranes, vehicle mounted cranes, and others. While there are many safety regulations related to cranes, in this meeting we will consider some basic principles of working with and around cranes that can keep us safe. As a reminder, only certified individuals can operate a crane. In addition, only use qualified signal persons and riggers.

**Group Discussion:** Have you ever seen an incident involving a crane? What happened?

**In our meeting, we will discuss:**

### (1) FATALITIES TO LEARN FROM

### (2) THE THREE BIGGEST HAZARDS

### (3) WORKING AROUND THEM

### FATALITIES TO LEARN FROM

**Fatality 1:** While lifting a large caisson with a crane, a shackle snapped causing it to fly approximately 30' away and strike an employee in the head. The employee was instantly killed. The shackle was not rated for the load being lifted.

**Group Discussion:** In addition, to using properly rated shackles, what can we learn from this?

**Fatality 2:** While using wire rope to lift steel beams (rope wrapped around the beams, the beams broke through and fell nearly 100' down crushing an employee below.

**Group Discussion:** What can we learn from this?

# THE THREE BIGGEST HAZARDS

1. **COLLAPSE:** It is a frightening sight when a crane collapses. It will damage property and can crush anyone in its way. When required maintenance and inspections are not performed, or the crane's capacity is exceeded, the crane can fail and collapse.
2. **FALLING OBJECTS:** When qualified riggers and proper rigging techniques are not used, rigging equipment is not rated for the load, or the equipment is not inspected, the load can fall. This highlights that no one should be in the swing and fall area of a crane and its load.
3. **CONTACT WITH ELECTRICAL LINES:** Every site should be evaluated for power lines. The best scenario is to de-energize the lines and follow LO/TO procedures. At least 10' clearance must be kept from live lines up to 50kv. If above 50kv, consult OSHA for the minimum distance. Always review the manufacturer's recommendations.

**Group Discussion:** What other hazards can you think of?

## WORKING AROUND THEM

Before any crane lift, a safety meeting should be held with all personnel involved with the lift. In addition, any others who could be affected by the lift should be informed of the lift. In addition:

- Ensure that the site has been evaluated for hazards and there is a safe location for crane set up.
- Ensure there is a lifting plan in place and all personnel are trained on it. Assign responsibilities and ensure all selected personnel are qualified (Example: Who will operate, rig, signal, land the load?)
- Call off the lift if anything is unsafe, including the weather.
- Delineate the crane, lift and swing area. Keep the area clear of personnel!

---

### Attendees Names

Fermin Salas

Rodolfo Medina

### Attendees Signatures



Rodolfo

## CONDUCTOR SIGNATURE

A handwritten signature in black ink, consisting of several overlapping, fluid strokes that form an abstract, cursive shape.

Copyright ©2018 Safety Compliance Company. All rights reserved. This document is intended as a safety tailgate meeting and does not contain all OSHA regulations. Please refer to OSHA and other state and federal agencies for further and current regulations. Not to be duplicated or distributed for use without the express written consent of Safety Compliance Company