



SAFETY TAILGATE MEETING

Generated by Safety Compliance App www.safetycompliance.com | www.safetycomplianceapp.com

Company	Pacific Hydrotech Corporation	Project	C2302 EMWD SJVRWRF		
Date	February 10, 2025	Time	6:41 AM	Conductor	Chuck Erickson

RIGGING SAFETY

INTRODUCTION

PLEASE REMEMBER: Only qualified riggers may perform rigging operations.

In this meeting, we will discuss:

- (1) Rigging Basics**
- (2) Rigging Safety Rules**

RIGGING BASICS

Rigging Safety Tips to Keep in Mind:

- Inspection of rigging slings is the responsibility of all employees engaged in crane/hoisting operations.
- Identifying damaged rigging may save lives and prevent damage of more equipment.
- Rigging should only be done by craftsmen who have had training in the use of tools and equipment used for moving of material on a job site.
- If untrained employees perform rigging operations, they may overlook some of the specific hazards associated with improper rigging or use rigging that may be damaged.
- Any employee that is aware of damaged rigging, i.e. wire rope, synthetic slings, chains, hooks, shackles, etc... should report them to the person in charge of the operation immediately.
- Slings should be immediately removed from service if any of these conditions are present. They should then be tagged as “Out of Service” and taken in for repair or destroyed completely if they cannot be repaired by a competent person.
- Do not allow anyone to walk under a suspended load – ever!
- Do not take chances with damaged rigging. The life you preserve may be yours or – your co-worker’s!

RIGGING SAFETY RULES

Here are a few safety tips that should be followed by anyone involved in rigging:

- Six randomly distributed broken wires in one lay of wire rope, or 3 broken wires in one strand in one lay.
- Wear or scraping on one-third the original diameter of the wire rope on the outside individual wires.
- Kinking, crushing, bird caging, or any other damage to the wire rope structure.
- Cuts, tears, or burns in synthetic slings or ropes.
- End attachments that are cracked, deformed, chaffed, or split.
- Indications of heating of wire rope, shackles, hooks, or chain.
- Significant corrosion of the sling, wire, chain, or end attachments. Never use defective hardware. Take defective hardware out of service immediately and follow your company's procedure for handling defective equipment.
- Missing safe working load (SWL) or identification tags.
- Hooks that have been opened more than fifteen percent of the normal throat opening measured at the narrowest point, or twisted more than ten degrees from the plane of the unbent hook.
- Be sure to establish the weight of the load.
- Determine the proper type of hitch based on the type of load.
- Understand the relationships between angles and tension as they pertain to slings and hardware. If you don't understand the relationships, or if you have any questions, check with your supervisor before you proceed.
- Make sure that you select the right sling for the job based on the type of load to be lifted.
- Also, select the right hardware based on the type of load and the type of sling or slings that will be used for the lift.
- As you rig the load, protect slings from cuts and tears.
- Determine the load's center of gravity.
- Pay close attention to detail at the time of the lift.

Attendees Names

Attendees Signatures

carlos alvarado



michael mcgregor



Cameron Williams



andres paniagua

N/A

Henry Walls Sr



Jesus Trullillo

N/A

Robert Lawler



brad groff



Henry WALLS



anthony freeman



Robert Hooper III

N/A

michael gurule

N/A

Fernando Mendez

N/A

Manuel Ordas

N/A

robert hooper

N/A

Francisco Trujillo



Porfirio Lopez



Chuck Erickson



Raymond Walls

N/A

Shawn Brady



Mark Morales

N/A

Yamil Ruelas

N/A

Julian Montellonee



Anthony Padilla



Fernando Sanchez

N/A

Salvador Ordaz

N/A

Francisco Murillo

N/A

Gabriel Rodriquez



Alejandro (Alex) Andrade



CONDUCTOR SIGNATURE



Copyright ©2018 Safety Compliance Company. All rights reserved. This document is intended as a safety tailgate meeting and does not contain all OSHA regulations. Please refer to OSHA and other state and federal agencies for further and current regulations. Not to be duplicated or distributed for use without the express written consent of Safety Compliance Company