

# SAFETY TAILGATE MEETING

Generated by Safety Compliance App www.safetycompliance.com | www.safetycomplianceapp.com

Company	Pacific Hydrotech Corporation		Project	C2406 San Jac	into-Uriel	
Date	January 28, 2025	Time	6:58	AM	Conductor	Roger Morehart

# LADDER SAFETY

## INTRODUCTION

When used correctly ladders can be an effective means to access work levels and to accomplish work. However, they are also dangerous. More falls occur from ladders than any other piece of equipment. To remain safe we must use them correctly and only after being trained and authorized to do so.

#### Group Discussion:

- Have you ever experienced or seen an injury from using a ladder?
- What happened? Why did it happen?
- What can we learn from it?

In this training we will dicsuss:

(1) INSPECTING LADDERS

- (2) USING LADDERS SAFELY
- (3) CHOOSING THE RIGHT LADDER

### **INSPECTING LADDERS**

All ladders must be inspected before each use, including:

- Ensure there is no damage, lack of structural integrity, missing components or loose parts.
- The steps or rungs must be in good condition, tight and secure to the side rails.
- Ensure movable parts operate correctly.
- They must be free of oil, grease, and other slippery materials.
- All manufacturer labeling must clearly be in place.
- Only set them up in a safe area for use.

Immediately remove damaged or unsafe ladders from service and notify your supervisor.

## USING LADDERS SAFELY

#### FOR SAFE USE:

- Maintain at least 3 points of contact when climbing or descending a ladder. (Two hands and a foot or two feet and a hand).
- To keep your hands free, do not carry material up or down ladders.
- Stay near the middle of the ladder, always face the ladder and never over reach.
- Only place ladders on a stable, level surface that is not slippery.
- Use barricades when necessary to keep traffic away from the ladder.
- Do not set up within 10' of a power line or use metal ladders near any electricity.
- Do not use a ladder for other than it is intended. For example, do not use a folded step ladder.
- Never climb above the top two steps of a ladder.
- Extension ladders are to be set up at a 4:1 pitch, extend at lest 3' above the platform of access, and be secured.

### **CHOOSING THE RIGHT LADDER**

Never exceed the weight limit! Only use Type 1, 1A, or 1AA ladders.

Type:	Weight Rating:	Duty Rating:
1-AA	375 pounds	Super Heavy Duty
1-A	300 pounds	Extra Heavy Duty
1	250 pounds	Heavy Duty Industrial
2	225 pounds	Medium Duty
3	200 pounds	Commercial
		Light Duty Household

Attendees Names Andreas Paniahua	Attendees Signatures N/A
Pedro Sanchez	N/A
Brent Pawley	N/A
Juan manrique	N/A
Parker Meeks	N/A

Donald Hutchinson	
Will Walker	
James Putt	
Jesus Trulillo	
robert hooper	
oswaldo barajas	
Brendon Whipple	

Anthony Sanchez

N/A

A





N/A



N/A

N/A

#### mike lauffer

#### Andrew Ingelno

#### Raymond Walls

#### David Vizcaino

#### Luis Valladolid

#### Luis Castrejon

Danny Alava

M. 44/9-





N/A



N/A



**Daniel Quintana** 



Anthony Hernandez	Gabriel Rodriquez	
	Anthony Hernandez	

## **CONDUCTOR SIGNATURE**

Copyright @2018 Safety Compliance Company. All rights reserved. This document is intended as a safety tailgate meeting and does not contain all OSHA regulations. Please refer to OSHA and other state and federal agencies for further and current regulations. Not to be duplicated or distributed for use without the express written consent of Safety Compliance Company

N/A N/A