



SAFETY TAILGATE MEETING

Generated by Safety Compliance App www.safetycompliance.com | www.safetycomplianceapp.com

Company	Ultimate Internet Access	Project	JV-2		
Date	August 09, 2024	Time	6:02 AM	Conductor	Carlos Aguilar

CAUGHT-IN OR BETWEEN HAZARDS

INTRODUCTION

Caught-in or between injuries are the result of crushing injuries in between objects. Before beginning specific tasks inspect both the equipment you use and the work area for hazards that could expose you to these types of injuries. Then take action to protect yourself and others.

We will discuss three of the ways caught-in or between injuries occur

(1) MACHINERY AND EQUIPMENT

(2) ROLLING, SLIDING OR SHIFTING OBJECTS

(3) TRENCH CAVE-INS

MACHINERY AND EQUIPMENT

A fingertip, hand, limb, or even an entire body can be caught in a pinch point. To prevent this, keep body parts and clothing a safe distance away from any pinch point and never place hands where you cannot see them.

Have you ever seen an injury occur where this was the hazard?

EXAMPLE: A worker was ripping a 6-inch piece of wood on an unguarded compound miter saw. His left thumb was caught in the saw and amputated.

What can we learn from this?

What equipment do we have where something similar could happen if a guard was removed?

ROLLING, SLIDING AND SHIFTING OBJECTS

Be aware of equipment around you and stay a safe distance from it. Never place yourself between moving equipment, potentially shifting materials, and an immovable structure such as a building.

- Have you ever seen an injury occur where this was the hazard?

EXAMPLE: A worker was operating a road grader when the engine died and the vehicle began to roll toward a small ravine. The employee jumped off the grader but was pulled under the grader as it overturned. He was killed when he was crushed underneath the tires.

What can we learn from this?

What equipment do we have where something similar could happen?

TRENCH CAVE-INS

When trench walls cave in they can crush or suffocate a worker. Consider: A cubic yard of soil weighs about 3,000 pounds!

If a trench is 5' or deeper a protective system, such as a trench shield, is required to prevent a cave-in. However, even trenches less than 5' in depth can cave in and trap a worker. All trenches must be inspected per OSHA regulations prior to working in them.

EXAMPLE: An employee and a co-worker were working in a 9-foot deep excavation installing water pipes, when the south side of the excavation caved in on the employee and buried him. The employee was killed.

What can we learn from this?

GROUP IMAGE

EMERGENCY 911



SITE SAFETY MEETING

FOREMAN: Amaro

JOB: Jump water DATE: 9/9/24

Personal Protective Equipment

- Steel Toe Boots YES / NO / N/A
- Reflective Safety Vest YES / NO / N/A
- Hard Hat YES / NO / N/A
- Gloves YES / NO / N/A
- Eye Protection YES / NO / N/A
- Rain Jacket & Pants YES / NO / N/A

Safety

- First Aid Kit YES / NO / N/A
- Fire Extinguisher YES / NO / N/A
- Water and Ice YES / NO / N/A
- CPR Certification Card YES / NO / N/A Expiration Date:
- Traffic Delineation Handbook / Traffic Control & Flagging Certification Card YES / NO / N/A Expiration Date:
- Heat Index App (OSHA-NIOSH Heat Safety Tool) YES / NO / N/A
- Traffic Cones (Paper 10# per 10mph) YES / NO / N/A
- Safety System # over 100 YES / NO / N/A
- Street Level Hazards Brief (Traffic, Pedestrians, Animals, etc) YES / NO / N/A
- Overhead Hazards Brief (Wires, Trees/ Limbs, etc) YES / NO / N/A
- Wet Grounds/Streets Brief (Slip Hazards, Reduce Vehicle Speed by 30%, etc) YES / NO / N/A
- Designated Shaded Rest Area YES / NO / N/A
- Confined Space Entry (Permit, Tripod/Winch, Body Harness, Blower, Gas Meter) YES / NO / N/A Competent Person:
- Trench Shoring (Shoring, Pump) YES / NO / N/A

Hospital [Nearest to Jobsite]

Name: Kaiser

Address: 2295 Vinograd
Ontario CA

Meeting Notes

Caught in or Between Hazards

ATTENDEES NAME	SIGNATURE
<u>Carlos Urrutia</u>	<u>[Signature]</u>
<u>Devin Ford</u>	<u>[Signature]</u>
<u>Dylan Merten</u>	<u>[Signature]</u>
<u>Miguel Cardoza</u>	<u>[Signature]</u>
<u>Pete Valdez</u>	<u>[Signature]</u>
<u>Lisando Briseno</u>	<u>[Signature]</u>
<u>Virgilio Barreno</u>	<u>[Signature]</u>
<u>Hector Gonzales</u>	<u>[Signature]</u>
<u>Isaac Duran</u>	<u>[Signature]</u>
<u>Raul Medel</u>	<u>[Signature]</u>
<u>Noe Delgado</u>	<u>[Signature]</u>
<u>Saul Nieves</u>	<u>[Signature]</u>

Hector Gonzales

Attendees Names

Carlos Urrutia

Devin Ford

Dylan Merten

Miguel Cardoza

Pete Valdez

Lisando Briseno

Virgilio Barreno

Hector Gonzales

Isaac Duran

Raul Medel

Noe Delgado

Saul Nieves

Attendees Signatures

N/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

Bryan Godinez-Lopez

N/A

Edwin Jaggli

N/A

Carlos Aguilar

N/A

Armando Aguilar

N/A

CONDUCTOR SIGNATURE



Copyright ©2018 Safety Compliance Company. All rights reserved. This document is intended as a safety tailgate meeting and does not contain all OSHA regulations. Please refer to OSHA and other state and federal agencies for further and current regulations. Not to be duplicated or distributed for use without the express written consent of Safety Compliance Company