

Results for: Lockout Tagout - Construction

Company Name: Documotion

Points: 70 out of 100

Duration: 2 min, 46 sec

Percentage:



Question 1 of 10

Types of hazardous energy include pneumatic, electrical and:

Correct answer: (A)

Selected answer: (C)

A) Thermal

B) Dissipation

C) All of the above

Question 3 of 10

The last step of de-energizing procedures is verify.

Correct answer: (A)

Selected answer: (A)

A) True

B) False

Employee Name: Devin Magrath

Title: Lockout Tagout - Construction

Date finished: May Thu May 2020 02:32

Date started: May Thu May 2020 02:30

Question 2 of 10

Step four of de-energizing lockout procedures is placing the lock.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

Question 4 of 10

In the fatality story, what type of hazardous energy killed the worker?

Correct answer: (B)

Selected answer: (B)

A) Gravitational

- B) Electrical
- C) Mechanical

Question 5 of 10

An electrical plug never needs to be locked out.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

Question 7 of 10

Step two of the re-energizing procedures is:

Correct answer: (A)

Selected answer: (A)

A) Remove

B) Notify

C) Check

Question 9 of 10

A tag that is placed with a lock must be blue and white.

Correct answer: (B)

Selected answer: (A)

A) True

B) False

Question 6 of 10

A lock does not need to placed on a circuit breaker as long as it is turned off and in clear view of the person working on it.

Correct answer: **(B)** Selected answer: **(B)**

A) True

B) False

Question 8 of 10

A "Do Not Operate" or "Do Not Use" tag must always be placed with a lock.

Correct answer: (A)

Selected answer: (A)

A) True

B) False

Question 10 of 10

If three people are performing repair work, only supervisor must place his lock and tag.

Correct answer: (B) Selected answer: (A)

A) True

B) False