

Results for:

**Lockout Tagout - Construction** 

**Company Name:** 

**RJ Noble** 

Points:

90 out of 100

Duration:

3 min, 21 sec

Percentage:

90.00%

**Employee Name:** 

Andrew Salcedo

Title:

Lockout Tagout - Construction

Date finished:

Jul Thu July 2021 10:00

Date started:

Jul Thu July 2021 09:56

#### Question 1 of 10

### Types of hazardous energy include pneumatic, electrical and:

Correct answer: (A)

Selected answer: (A)

A) Thermal

B) Dissipation

C) All of the above

### Question 2 of 10

## Step four of de-energizing lockout procedures is placing the lock.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

### Question 3 of 10

### The last step of de-energizing procedures is verify.

Correct answer: (A)

Selected answer: (A)

A) True

B) False

#### Question 4 of 10

# In the fatality story, what type of hazardous energy killed the worker?

Correct answer: (B)

Selected answer: (B)

A) Gravitational

B) Electrical

C) Mechanical

### Question 5 of 10

An electrical plug never needs to be locked out.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

Question 6 of 10

A lock does not need to placed on a circuit breaker as long as it is turned off and in clear view of the person working on it.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

### Question 7 of 10

Step two of the re-energizing procedures is:

Correct answer: (A)

Selected answer: (B)

A) Remove

B) Notify

C) Check

### Question 9 of 10

A tag that is placed with a lock must be blue and white.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

#### Question 8 of 10

A "Do Not Operate" or "Do Not Use" tag must always be placed with a lock.

Correct answer: (A)

Selected answer: (A)

A) True

B) False

### Question 10 of 10

If three people are performing repair work, only supervisor must place his lock and tag.

Correct answer: (B)

Selected answer: (B)

A) True

B) False