Results for:
Fire Prevention & Hot Work

Company Name:
Tiller Constructors

Points:
90 out of 100

Duration:
1 min, 59 sec

Percentage:

90.00%

Employee Name:
Christian De Jesus Bollas Velasco

Title:
Fire Prevention & Hot Work

Date finished:
Nov Wed November 2023 06:04

Date started:
Nov Wed November 2023 06:02

Question 1 of 10

The four parts of the fire tetrahedron are oxygen, fuel, heat, and a self sustaining chemical chain reaction.

Correct answer: **(A)**

Selected answer: **(A)**

A) True

B) False

Question 2 of 10

An effective tool to use to prevent fires is a

Correct answer: **(B)**

Selected answer: **(B)**

A) A building permit

B) Hot work permit

Question 3 of 10

How long must a person perform a fire watch after hot work is finished?

Correct answer: **(B)**

Selected answer: **(C)**

A) 15 minutes

B) 30 minutes

C) 2 hours

Question 4 of 10

Tasks that are considered hot work include soldering, welding and cutting with an abrasive wheel

Correct answer: **(A)**

Selected answer: **(A)**

A) True

B) False

In the video, a 9 volt battery and steel wool was used to teach how overloading electrical circuits can start fires

Correct answer: **(A)**

Selected answer: **(A)**

A) True

B) False

A class A fire extinguisher is designed to put out an electrical fire

Correct answer: **(B)**

Selected answer: **(B)**

A) True

B) False

The P.A.S.S. technique should be used when using a fire extinguisher to put out a small fire.

Correct answer: **(A)**

Selected answer: **(A)**

A) True

B) False

What part of a fire should you aim for when using a fire extinguisher safely?

Correct answer: **(C)**

Selected answer: **(C)**

A) the top of the fire

B) the middle of the fire

C) the base of the fire

Used solvent rags must be stored in an approved safety container

Correct answer: **(A)**

Selected answer: **(A)**

A) True

B) False

Fire extinguishers must be inspected every two months

Correct answer: **(B)**

Selected answer: **(B)**

A) True

B) False