

Results for:

Fall Protection Safety

**Company Name:** 

Bay City Boiler

Points:

70 out of 100

Duration:

1 min, 4 sec

Percentage:

70.00%

**Employee Name:** 

Joe Moran

Title:

Fall Protection Safety

Date finished:

May Fri May 2024 08:58

Date started:

May Fri May 2024 08:57

#### Question 1 of 10

# Federal OSHA generally requires fall protection if a worker is exposed to a fall distance of how far?

Correct answer: (B)

Selected answer: (B)

A) 5'

B) 6'

### Question 2 of 10

## In the Hierarchy of Fall Protection, it is better to use:

Correct answer: (A)

Selected answer: (B)

A) Fall Restraint

B) Fall Arrest

#### Question 3 of 10

ט) 8

#### It is best if a fall hazard can be eliminated

Correct answer: (A)

Selected answer: (A)

A) True

B) False

#### Question 4 of 10

A personal fall arrest system consists of an anchor, a harness, and a connecting device.

Correct answer: (A)

Selected answer: (A)

A) True

B) False

#### Question 5 of 10

Inspection of personal fall protection equipment should be done before each use.

Correct answer: (A)

Selected answer: (A)

A) True

B) False

#### Question 7 of 10

The D-ring on a harness should be at a workers waist.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

#### Question 9 of 10

Training is required before using a personal fall system.

Correct answer: (A)

Selected answer: (A)

A) True

B) False

#### Question 6 of 10

Falls are not the leading cause of construction fatalities.

Correct answer: (B)

Selected answer: (B)

A) True

B) False

#### Question 8 of 10

If using a personal fall arrest system, OSHA says a worker cannot free fall more than 6' or hit an object below.

Correct answer: (A)

Selected answer: (B)

A) True

B) False

#### Question 10 of 10

An anchor used as part of a fall arrest system must be rated for at least 10,000 pounds per person.

Correct answer: (B)

Selected answer: (A)

A) True

B) False